LIFT PLAN INFORMATION

1. Please fill out Completely. Note: Any changes in the crane configuration, placement, rigging lifting, lifting scheme or calculations may require that a ne Lift Plan be developed. Project Name:
Company Name: Date:
Location of Lift:
2. Description of Lift: (Goal of operation, how operation will be performed, where it will occur)
3. Please Check Off & Include the Following Documents:
 □ Written Lift Description (above) □ Rigging sketch w/component detail □ Orientation of Crane to the Load - sketch □ Spreader Beam / Lifting drawing (w/engineering) □ Sketch showing C/G of Load - side view □ Layout Plan
Overhead view of Operation - sketch CRANE'S LOAD CHART, WITH APPLICABLE WEIGHTS HIGHLIGHTED ATTACHED.
A. Crane Configuration Crane Manufacturer
Max Load Radius: ft. or (Angle) Pick-up: ft. or (Angle) Set-down: ft. or (Angle) Crane Capacity at max. Radius: Over rear (Ibs.): Over side (Ibs.): Over front (Ibs.): Maximum boom length for operation (ft.): Required Counterweight: Weight (in Ibs.):
Sope diameter & type: Number of parts: Hoist Capacity: Wire rope limit (in lbs.): Line pull per part: JACOBS

	LIFT PLAN INFORMATION pg 2
7. Rigging	
Rigging connection to load: Fixed point Free connection	Spreader capacity: Sling Size/Capacity: Sling Material: Maximum force on sling legs (lbs.): Connecting hardware capacity (lbs.):
8. Total Gross Load	
Total Deductions from Capacity	Deductions
Wire rope in excess of rated capacity for lift (ft.):	Block Weight:
Wire Rope below Grade (ft.):	e weight: Over Haul Ball Weight: Auxiliary Boom Head:
Net Load Weight	Ext. or Jib Weight:
Load weight include method of determining load weight, if estir	nated - specify estimator, if Main Hoist Line Wt:
measured - specify scale type: Estimated By Whom:	Aux. Hoist Line Wt:
Measured / Scale:	Rigging Weight:
	Total Deductions A
NetLoad + Deductions	= Total Gross Load (TGL) *
Net Load + Deductions *TGL ÷ Rated Capacity	= Total Gross Load (TGL) * = Capacity margin %
	- Total Gloss Load (TGL)
	- Total Gloss Load (TGL)
*TGL ÷ Rated Capacity	- Total Gloss Load (TGL)
*TGL ÷ Rated Capacity 9. Area of Operations Crane ground bearing pressure (psf.):	= Capacity margin
*TGL	= Capacity margin
*TGL ÷ Rated Capacity 9. Area of Operations Crane ground bearing pressure (psf.): Matting necessary for ground conditions (dimensions): Max Boom Length for Travel (based on Manufacturers limitate)	= Capacity margin
*TGL Rated Capacity 9. Area of Operations Crane ground bearing pressure (psf.): Matting necessary for ground conditions (dimensions): Max Boom Length for Travel (based on Manufacturers limitated Clearance from Overhead Obstructions (ft.):	= Capacity margin
*TGL ÷ Rated Capacity 9. Area of Operations Crane ground bearing pressure (psf.): Matting necessary for ground conditions (dimensions): Max Boom Length for Travel (based on Manufacturers limitate)	= Capacity margin
*TGL Rated Capacity 9. Area of Operations Crane ground bearing pressure (psf.): Matting necessary for ground conditions (dimensions): Max Boom Length for Travel (based on Manufacturers limitated Clearance from Overhead Obstructions (ft.):	= Capacity margin
*TGL • Rated Capacity 9. Area of Operations Crane ground bearing pressure (psf.): Matting necessary for ground conditions (dimensions): Max Boom Length for Travel (based on Manufacturers limitated Clearance from Overhead Obstructions (ft.): Head room requirements: Head room remains	= Capacity margin
*TGL ÷ Rated Capacity 9. Area of Operations Crane ground bearing pressure (psf.): Matting necessary for ground conditions (dimensions): Max Boom Length for Travel (based on Manufacturers limitated Clearance from Overhead Obstructions (ft.): Head room requirements: Head room remains Head room r	= Capacity margin
*TGL *Rated Capacity 9. Area of Operations Crane ground bearing pressure (psf.): Matting necessary for ground conditions (dimensions): Max Boom Length for Travel (based on Manufacturers limitated Clearance from Overhead Obstructions (ft.): Head room requirements: Head room remains Head room	= Capacity margin
*TGL • Rated Capacity 9. Area of Operations Crane ground bearing pressure (psf.): Matting necessary for ground conditions (dimensions): Max Boom Length for Travel (based on Manufacturers limitated Clearance from Overhead Obstructions (ft.): Head room requirements: Head room remains 10. Wind Limitations Record Crane wind restriction from the load chart: 11. Crew How many personnel are required, what are their jobs, where will they be	= Capacity margin
*TGL *Rated Capacity 9. Area of Operations Crane ground bearing pressure (psf.): Matting necessary for ground conditions (dimensions): Max Boom Length for Travel (based on Manufacturers limitated Clearance from Overhead Obstructions (ft.): Head room requirements: Head room remains Head room	= Capacity margin